



Type	Capacity (Mcal)	Capacity (kW)	Water vol. (Ltr.)	Weight (kg)	H.S. (m2)	Gassided Vol. (m3)	dp (mmWC)	A	B1	B2	C	D	E	F	G	H	J	K	M	N	R	S	U	Excellent Cond. TYPE
CET 12	1000	1200	9350	7050	74	3,0	85	5710	6615	7496	1900	2340	1243	1100	300	1100	DN125-PN6	2x2"	2"	2390	420	2624	1243	L12C
CET 18	1500	1800	11500	8850	100	4,5	85	6250	7155	8036	2050	2490	1318	1250	350	1250	DN150-PN6	2x2"	2"	2540	420	2792	1318	L18C
CET 24	2000	2400	14250	10700	123	6,0	95	6752	7657	8654	2200	2640	1412	1350	450	1350	DN150-PN6	2x2"	2"	2690	580	2886	1412	L24C
CET 30	2500	3000	16000	11900	136	7,5	95	7032	7937	9069	2300	2740	1462	1450	450	1450	DN200-PN6	2x2"	2"	2790	580	2988	1462	L30C
CET 36	3000	3600	17650	13200	157	9,0	95	7270	8175	9307	2400	2840	1512	1550	500	1600	DN200-PN6	3x2"	2"	2890	580	3138	1512	L36C
CET 42	3500	4200	18800	14200	175	10,2	95	7581	8486	9774	2450	2890	1537	1600	550	1600	DN200-PN6	3x2"	2"	2940	580	3218	1537	L42C
CET 48	4000	4800	20700	15400	194	12,0	95	7821	8726	10072	2550	2990	1587	1700	600	1600	DN200-PN6	3x2"	2"	3040	580	3268	1587	L48C
CET 60	5000	6000	23500	19950	237	16,2	95	8825	9730	11270	2650	3090	1637	1828	650	1700	DN250-PN10	4x2"	2"	3140	700	3308	1637	L60C
CET 72	6000	7200	25500	21850	261	18,1	95	8840	9745	11285	2750	3190	1706	1900	700	1800	DN250-PN10	2xDN80-16	2"	3240	700	3377	1706	L72C
CET 84	7000	8400	25700	22750	279	19,7	95	8870	9775	11572	2800	3240	1731	1982	700	1900	DN250-PN10	2xDN100-16	2,5"	3290	830	3382	1731	L84C
CET 96	8000	9600	26300	23700	289	21,7	100	9396	10301	12098	2800	3240	1731	2000	800	1900	DN250-PN10	2xDN100-16	2,5"	3290	830	3552	1731	L96C
CET 108	9000	10800	28600	24000	311	23,9	100	9885	10790	12763	2850	3290	1756	2032	850	1900	DN300-PN10	2xDN100-16	2,5"	3340	830	3572	1756	L108C
CET 120	10000	12000	30300	25750	323	26,1	100	10150	11055	13028	2900	3340	1781	2086	950	1950	DN300-PN10	2xDN100-16	2,5"	3390	830	3602	1781	L120C
CET 140	12000	14000	33300	30100	372	30,9	110	10400	11305	13452	3050	3490	1856	2236	950	2000	DN300-PN10	2xDN125-16	2,5"	3540	830	3727	1856	L140C



Grote Esch 400  
2841 MJ Moordrecht (NL)

Tel. +31(0)182 614 482 | e-mail : info@fchrone.nl  
fax +31(0)182 633 257 | website : www.fchrone.eu

-Flange connections up to/incl. DN200 acc. EN1092-1 PN6 from DN250 acc. EN1092-1 PN10  
-The boilers are provided with 2 lifting lugs.  
-Flange connections safety valves acc. EN1092-1 PN16

Modifications reserved 2-2019